EC

MAXX Bendurol2

ALLROUND FLOOR STRIPPER

Performance

- ▲ Effective removal of multi-layer polymer films
- Low foaming formula based on a new generation of raw materials with excellent biodegradable properties

Efficiency

- ▲ Rinse free and fast acting formula saves labour and energy costs
- Well suited for deep cleaning tasks thanks to outstanding dirt removal properties

Safety

- ▲ Anti-slip effect during stripping for increased work place safety
- ▲ Excellent material compatibility



Use instructions



1. Check hygiene plan and product label for detailed use information.



2. Wear suitable protective clothing when handling the product.



3. For stripping of coatings dilute MAXX Bendurol2 1:1 to 1:3 with cold water in a bucket or in a single disc machine tank.



4. Apply the solution to the floor.



5. Leave the solution to act for 6. Scrub the floor thoroughly at least 5 minutes.



with a single disc machine.



7. Remove the dilution with a wet vacuum cleaner, then mop once with clean water.



8. No rinsing required.

Application area

For all water- and alkali-resistant floor coverings except wooden floors, laminate and textile coverings. Ideally suited for linoleum coverings.

Special notes

- ▲ Test material compatibility in a small inconspicuous area prior to application.
- For floor cleaning, position warning signs "Attention wet floor" and leave in place until surface is totally dry.
- pH Value (conc): 10.1 10.6
- For professional use only.

Safety information

- Do not mix with any other product.
- For further information and safety instructions, please see product label and Safety Data Sheet.

Storage conditions

✓ Store between -5 °C and 40 °C in original closed container only.

pH Value



Worldwide Headquarter 1 Ecolab Place, St. Paul, MN55102 1.800.35.CLEAN European Headquarter Ecolab Europe GmbH Richtistr, 7 CH-8304 Wallisellen

Pack size

Product	Article No.	Pack size	
MAXX Bendurol2	9093750	2 x 5 L	

